

Trowel Grade Crack Filler

Trowel Grade Asphalt Emulsion Crack Filler

- Fills Cracks & Ruts in Asphalt Driveways
- Seals Out Moisture
- Easy To Apply
- Dries Black



Revised: 11/10

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

Heavy-bodied sand-filled trowel grade asphalt emulsion crack filler designed for filling cracks up to 1" wide in asphalt pavement surfaces. Can also be used to fill shallow ruts and depressions in pavement surfaces.

Uses

- Filling Cracks & Ruts in Asphalt Pavement
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

Surface Preparation

Surface should be dry, clean of dirt and loose of foreign material.

Application

For best results, depressions should be built up in layers of 3/8 inch maximum. Material can be spread using trowel or squeegee. Allow to cure at least 24 hours prior to sealing or other use.

Drying Time

Drying time is dependent upon depth of application.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 40 °F within a 24 hour period.

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Coverage will vary, depending on width and depth of area.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 40 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Trowel Grade Crack Filler
Trowel Grade Asphalt Emulsion Crack Filler

Form No.: FP-TD15581

Packaging

Item #	Container Size	Pack	Weight
15581	.9 Gallon	6	77.82

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Silica Sand	14808-60-7
Asphalt	8052-42-4
Hydrous Aluminum Silicate	1332-58-7
Magnesium Aluminum Silicate	12174-11-7
Water	7732-18-5