

Non-Fibered Fence & Foundation Coating

Asphalt Based Sealer/Preservative

- Penetrates, Preserves & Protects Most Foundations, Wood Fences, Barns & More
- Use Above or Below Grade
- Meets ASTM D 41
- Dries Black



Revised: 07/23

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

A cold-applied, liquid asphalt in a solvent system ideal for waterproofing above and below grade exterior concrete, masonry walls, and foundations that are completely dry. Also may be used as a coating for fences and barns.

Uses

- Concrete Foundations
- Wood Fences & Barns

Surface Preparation

Surface must be clean, dry, and free of moisture both on and beneath the surface.

Application

Stir FarmPaint.com Non-Fibered Fence and Foundation Coating thoroughly. Apply a single coat over the entire surface with a brush, roller, or airless spray unit.

Drying Time

Up to 24 hours depending on weather conditions and thickness of application.

Clean Up

Clean tools with mineral spirits or waterless hand cleaner before material has dried.

Weather Conditions

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Concrete & Masonry Surfaces: 50-65 sq. ft. per gallon
- Wood or Composition: 65-90 sq. ft. per gallon

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat or Thin
- Keep Away from Heat and Flame
- Do Not Store at Temperatures Above 100 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Non-Fibered Fence & Foundation Coating
Asphalt Based Sealer/Preservative

Form No.: FP-TD19525

Packaging

Item #	Container Size	Pack	Weight
19527	55 Gallon Drum	1	475 lbs.
19525	4.75 Gallon Pail	1	42 lbs.
19521	.9 Gallon Pail	6	47 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7